

## TEST REPORT

No. : GZMR090404097

Date : Apr 03, 2009

Page: 1 of 2


HUDONG MEIXIN PLASTIC LUMBER PRODUCTS MANUFACTURING CO., LTD  
NGA INDUSTRIAL PARK, DALING, HUDONG, GUANGDONG PROVINCE, PRC

The following sample(s) was/ were submitted and identified on behalf of the client as:

Sample Name : NEWTECHWOOD  
Sample Information : 090113-1  
SGS Ref No. : GP090400526-8.5  
Test Performed : Selected test(s) as requested by applicant  
Date of Receipt : Apr 02, 2009  
Test Period : Apr 02, 2009 to Apr 03, 2009  
Test result(s) : Please refer to the following page(s)

\*\*\*\*\*To be continued\*\*\*\*\*

Signed for and on behalf of  
SGS-CSTC Ltd.

  
Cathy Peng

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not engage the parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full without prior approval of the Company.



## TEST REPORT

No. : GZMR090404097

Date : Apr 03, 2009

Page: 2 of 2

Technical Supervisor

Test Result(s):

Sample description: Grey sheet

Test item: Tensile strength

Test method: ASTM D638-08

Specimen: Type I

Speed: 5mm/min

Tensile strength: 21.8MPa

Note: 1. Test specimens were cut from sample.

2. This report is the English version of No.GZMR090303170.

\*\*\*\*\*End of report\*\*\*\*\*

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at <http://www.sgs.com/terms.and.conditions.htm>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full without prior approval of the Company.